

## IP66 LED Waterproof Luminaires



Produkt-Nummer	YL08-20W-600	YL08-20W-1200	YL08-36W-1200	YL08-45W-1200	YL08-36W-1500	YL08-54W-1500	YL08-65W-1500
Certifikat	CE EMC ROHS GS CB ENEC SAA C-TICK IK10 IP66 GWT850						
Input Voltage(V)	220-240VAC 50/60Hz						
Opal diffuser material	PC						
Body material	PC						
Body colour	Grå						
Clips	Stainless steel clips						
Terminal Block	3P screw terminal						
Driver brand	OSRAM/TRIDONIC/PHILIPS led driver ( for 20w, only can use TRIDONIC or PHILIPS led driver)						
LED brand	LG 2835						
LED type	SMD 2835						
LED Antal (PCS)	102	102	176	221	176	272	322
Ljuskärl	3000K,4000K,5000K,6500K						
CRI	> 80						
Typical Lumens with opal diffuser (+/-3%)	2600	2600	4680	5850	4680	7020	8450
Lighting Efficiency (Lm/W) with opal diffuser (+-3%)	130LM/W						
Power Factor	> 0.9						
Ljusvinkel:	120						
IP rating	IP66						
Garanti	5 år						
Product mått (mm)	650X90X69	1220X90X69			1560X90X69		

**Supply** Decor Lighting Gbg AB Adress: Utmarksvägen 8, 442 39 Kungälv  
Ordermail: [order@litealight.com](mailto:order@litealight.com) Hemsida: [litealight.com](http://litealight.com) Tel. 031-221150